

CBD15/18/20J-Li3 ▶



Characteristics

- Compact and flexible.
- Built-out charger.
- Metal cover.
- Portable lithium-battery.
- Option: smart handle.

| Model | | CBD15J-Li3 | | CBD18J-Li3 | | CBD20J-Li3 | | |
|--|----------|------------|-------|------------|-------|------------|-------|-------|
| Loading capacity | kg | 1500 | | 1800 | | 2000 | | |
| Load center | mm | 600 | | 600 | | 600 | | |
| Operating type | | Walkie | | Walkie | | Walkie | | |
| Wheels type | | PU | | PU | | PU | | |
| Driving wheel size | Φ×w (mm) | Φ210×70 | | Φ210×70 | | Φ210×70 | | |
| Max.lifting height | mm | 200 | | 200 | | 200 | | |
| Width of forks | mm | 550/685 | | 550/685 | | 550/685 | | |
| Fork length | mm | 1150 | | 1150 | | 1150 | | |
| Fork width | mm | 150 | | 150 | | 150 | | |
| Fork thickness | mm | 50 | | 50 | | 50 | | |
| Overall width | mm | 550/685 | | 550/685 | | 550/685 | | |
| Overall height(With handle) | mm | 1145 | | 1145 | | 1145 | | |
| Min.Turning radius | Wa (mm) | 1345 | | 1345 | | 1345 | | |
| Aisle width with pallet 1000 x 1200 across forks | Ast (mm) | 1750 | | 1750 | | 1750 | | |
| Travel speed,laden/unladen | km/h | 4.2/4.5 | | 4.2/4.5 | | 4.2/4.5 | | |
| Maximum climbing ability, with/without load | % | 5/10 | | 5/10 | | 5/10 | | |
| Drive motor | kW | 0.75 | | 0.75 | | 0.75 | | |
| Lift motor | kW | 0.8 | | 0.8 | | 0.8 | | |
| Battery voltage/rated capacity | V/Ah | 24/20 | 24/30 | 24/20 | 48/15 | 48/20 | 48/15 | 48/20 |
| Controller | | CURTIS | | CURTIS | | CURTIS | | |
| Battery weight (± 5%) | kg | 5.5 | 7 | 8.2 | 7 | 8.2 | 7 | 8.2 |
| Service weight with battery | kg | 144 | 145 | 146 | 155 | 156 | 157 | 158 |

