

CESAB PRODUCT RANGE

Counterbalanced and Warehouse Equipment



COUNTERBALANCED

3-wheel electric trucks



B210 - 213 - 215

 1.0t-1.25t-1.5t
 6470 mm
 24V / 1000Ah



B315 - 316 - 316L - 318 - 318L - 320

 1.5t-1.6t-1.8t-2.0t
 7470 mm
 48V / 750Ah

4-wheel electric trucks



B415 - 416 - 416L - 418 - 418L - 420

 1.5t-1.6t-1.8t-2.0t
 7470 mm
 48V / 750Ah



B620 - 625 - 625L - 630 - 630L - 635

 2.0t-2.5t-3.0t-3.5t
 6500 mm
 80V / 775Ah



B640 - 645 - 650

 4.0t-4.5t-5.0t
 6500 mm
 80V / 930Ah

Compact electric trucks



cenTAURO 48 160L - 200L

 1.6t-2.0t
 6970 mm
 48V / 840Ah



cenTAURO 80 250 - 300

 2.5t-3.0t
 6860 mm
 80V / 735Ah

Heavy duty electric truck



B860 - 870 - 885

 6.0t-7.0t-8.5t
 6450 mm
 80V / 1250Ah

COUNTERBALANCED

4-wheel engine trucks torque converter



M315 - 318

	1.5 t - 1.8 t
	6970 mm
	DIESEL / LPG



M320 - 325

	2.0 t - 2.5 t
	6970 mm
	DIESEL / LPG



M330 - 335

	3.0 t - 3.5 t
	6970 mm
	DIESEL / LPG

4-wheel engine trucks hydrostatic



Drago 150 - 180 - 200

	1.5 t - 1.8 t - 2.0 t
	6170 mm
	DIESEL / LPG



Drago H 250 - 300 - 350

	2.5 t - 3.0 t - 3.5 t
	7960 mm
	DIESEL / LPG



Drago E 250 - 300 - 350

	2.5 t - 3.0 t - 3.5 t
	7960 mm
	DIESEL / LPG

Legend

	Rated capacity		Additional info
	Maximum lifting height		Fuel type
	Maximum battery capacity		Nominal draw-bar pull

WAREHOUSE EQUIPMENT

Hand pallet trucks



CE200 - 230 - 300

-  2.0 t - 2.3 t - 3.0 t
-  The 2.3 t model is also available with low forks, quicklift feature and handbrake. Low forks are standard on the 2.0 t model.



CE200ST

-  2.0 t
-  Stainless steel version.



H210 - 210E

-  1.0 t
-  800 mm
-  Manual and electric scissor lifters.

Powered pallet trucks



P113

-  1.3 t
-  24V / 63 Ah



P214 - 216 - 218 - 220 - 225

-  1.4 t - 1.6 t - 1.8 t - 2.0 t - 2.5 t
-  24V / 300 Ah
-  Optional operator platform available for P220.



P320 - 322

-  2.0 t - 2.2 t
-  24V / 600 Ah
-  Available with a choice of travel speed (6, 8, 10 km/h).

Reach trucks



R112 - 114 - 116

-  1.2 t - 1.4 t - 1.6 t
-  8500 mm
-  48V / 620 Ah
-  Also available as a drive-in version with narrow overhead guard.



R212 - 214 - 216

-  1.2 t - 1.4 t - 1.6 t
-  8500 mm
-  48V / 620 Ah
-  Also available as a cold store version as well as drive-in version with narrow overhead guard.



R314 - 316 - 318 - 320 - 325

-  1.4 t - 1.6 t - 1.8 t - 2.0 t - 2.5 t
-  12500 mm
-  48V / 930 Ah
-  Also available as a cold store version, with or without heated cabin, as well as a drive-in version with narrow overhead guard.

Powered stacker trucks



S110 - 110S

-  1.0 t
-  2000 mm
-  24V / 63 Ah
-  S110S: straddle support arm version.



S210 - 212 - 214

-  1.0 t - 1.2 t - 1.4 t
-  4755 mm
-  24V / 300 Ah
-  Optional operator platform available.



S215 - 216 - 220

-  1.45 t - 1.6 t - 2.0 t
-  6000 mm
-  24V / 500 Ah
-  Available with a choice of chassis width.



S208L

-  0.8 t
-  1580 mm
-  24V / 230 Ah
-  Can lift up to 2000 kg when lifting with the support arms only. Available with optional automatic height adjustment.



S212L - 214L

-  1.2 t - 1.4 t
-  4755 mm
-  24V / 300 Ah
-  Elevating support arms. Optional operator platform available.



S215L - 216L - 220L

-  1.45 t - 1.6 t - 2.0 t
-  6000 mm
-  24V / 500 Ah
-  Elevating support arms.



S220D

-  1.0 t
-  2100 mm
-  24V / 300 Ah
-  Double stacker, lifts 800 + 1200 kg lifting with forks + support arms or 2000 kg when lifting with the support arms only. Optional operator platform available.



S212S

-  1.2 t
-  4755 mm
-  24V / 300 Ah
-  Straddle support arms. Optional operator platform also available.



S214S

-  1.4 t
-  5350 mm
-  24V / 500 Ah
-  Straddle support arms.



S312 - 314 - 316 - 320

-  1.2 t - 1.4 t - 1.6 t - 2.0 t
-  6000 mm
-  24V / 500 Ah
-  Available with a choice of speeds up to 10km/h.



S312L - 314L - 316L - 320L

-  1.2 t - 1.4 t - 1.6 t - 2.0 t
-  6000 mm
-  24V / 500 Ah
-  Elevating support arms. Available with a choice of speed, up to 10km/h.



S314S

-  1.4 t
-  5350 mm
-  24V / 500 Ah
-  Straddle support arms.

The data in this specification sheet was determined based on our standard testing conditions. Operating performance may vary depending on the actual specification and condition of the truck as well as the condition of the operating area. Availability and specifications are determined regionally and are subject to change without notice. Please consult your authorised CESAB dealership for further details. RANGE_EN_2015 / P&B RANGE V51 – Copyright CESAB Material Handling Europe.



HALA
LIFTING ^ MOVING > LEADING

Hala Equipment Trading LLC
Dubai Tel +971 4 284 7878, PO Box 410516
Warehouse No.8, Near Tasjeel, Al Qusais
Sharjah Tel +971 6 534 3325, PO Box 34337
Industrial Area 10
Abu Dhabi Tel +971 56 494 1057, Mussafah
sales@halaheavy.com

